

# SLI029075CW\_PW

SLI029075CW\_PW

---

IP65

IK07



---

Power	<b>20 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>1650 lm (120°)</b>	Colour temperature	<b>6000 K</b>
Colour of light	<b>CW</b>	Beam angle	<b>100 °</b>
IK	<b>07</b>	Degree of protection (IP)	<b>IP65</b>

---

## Technical data

---

Code	SLI029075CW_PW
Power	20 W
Nominal current	95 mA
Voltage	230 V
Energy consumption	20 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	1650 lm (120°)
Luminous flux**	1650 lm (360°)
Lamp efficacy	83 lm/W
Colour temperature	6000 K
Colour of light	CW
Beam angle	100 °
RA	>70
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, GLASS
IK	07
Degree of protection (IP)	IP65
Colour	White
Dimension (AxBxC)	116x92x24 mm
For use	Outside
Assembly method	On the ceiling
Application	EXT
Made in	PRC

## Related documents

---



 User manual



 Declaration of Conformity

