

# SLI035067NW\_PW\_IP44

SLI035067NW\_PW\_IP44



Power	<b>40 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>5300 lm (360°)</b>	Colour temperature	<b>4000 K</b>
Colour of light	<b>Neutral white</b>	Beam angle	<b>120 °</b>
Degree of protection (IP)	<b>IP44/IP20***</b>		

## Technical data


---

Code	SLI035067NW_PW_IP44
Power	40 W
Nominal current	185 mA
Voltage	230 V
Energy consumption	40 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	5300 lm (360°)
Luminous flux**	4800 lm (360°)
Lamp efficacy	133 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	120 °
RA	>80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum/Plastic
Degree of protection (IP)	IP44/IP20***
Colour	White
Dimension (AxBxC)	295x1195x32 mm
For use	Inside
Assembly method	On the ceiling, Recessed
Application	INT
Made in	PRC

## Related documents

---



 Declaration of Conformity