

# SYSTEM SHIFT BASIC GLOBE

WLD+70036WW

On track luminaire SYSTEM SHIFT BASIC GLOBE, with a power of 10 W, high light efficacy 102 lm/W. Designed to be mounted on a track.



Power	<b>10 W</b>	Voltage	<b>48 V</b>
Colour temperature	<b>2700 K</b>	Colour of light	<b>WW</b>
Beam angle	<b>120 °</b>	Degree of protection (IP)	<b>IP20</b>

## Technical data

---

Code	WLD+70036WW
Power	10 W
Nominal current	200 mA
Voltage	48 V
Energy consumption	10 kWh/1000h
Frequency	DC Hz
Protection class	III
Power factor	1
Useful luminous flux*	1020 lm (360°)
Luminous flux**	625 lm (360°)
Lamp efficacy	102 lm/W
Colour temperature	2700 K
Colour of light	WW
Beam angle	120 °
RA	80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 to +40 °
Lifespan	17000 h
Housing material	AL+PC
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	90x150 mm
For use	Inside
Assembly method	NA SZYŃĘ
Application	Inside
Made in	PRC

## Related documents

---



 User manual



 Declaration of Conformity